


Ronds laminés à chaud

Hot rolled round steel bars



Désignation		Diamètre	
	Kg / m	d mm	A mm ² x10 ²
R 10	0,617	10	0,785
R 12	0,888	12	1,13
R 14	1,210	14	1,54
R 16	1,580	16	2,01
R 18	2,000	18	2,54
R 20	2,470	20	3,14
R 22	2,980	22	3,8
R 24	3,550	24	4,52
R 25	3,850	25	4,91
R 26	4,170	26	5,31
R 27	4,490	27	5,73
R 28	4,830	28	6,16
R 30	5,550	30	7,07
R 32	6,310	32	8,04
R 34	7,130	34	9,08
R 35	7,550	35	9,62
R 36	7,990	36	10,2
R 38	8,900	38	11,3

Désignation		Diamètre	
	Kg / m	d mm	A mm ² x10 ²
R 40	9,860	40	12,6
R 42	10,900	42	13,9
R 45	12,500	45	15,9
R 50	15,400	50	19,6
R 55	18,700	55	23,8
R 60	22,200	60	28,3
R 65	26,000	65	33,2
R 70	30,200	70	38,5
R 75	34,700	75	44,2
R 80	39,500	80	50,3
R 85	44,500	85	56,7
R 90	49,900	90	63,6
R 95	55,600	95	70,9
R 100	61,700	100	78,5
R 105	68,000	105	86,6
R 110	74,600	110	95
R 120	88,800	120	113
R 130	104,000	130	133